

SPECIFICATIONS

DCD-1290/2060

DCD-2060G

AUDIO

No. of Channels: 2 channels
 Frequency Response: 2 ~ 20,000 Hz
 Dynamic Range: 100 dB
 Signal-to-Noise Ratio: 110 dB
 Harmonic Distortion: 0.0025% (1 kHz)
 Separation: 105 dB (1 kHz)
 Wow & Flutter: Below measurable limit: (±0.001% W. peak)
 Output (Analog): FIX. 2.0 V, VARIABLE 0 ~ 2.0 V
 (Digital): COAXIAL (0.5 Vp-p 75 ohm)
 OPTICAL

DISCS

Compact Disc format

GENERAL CHARACTERISTICS

Power Supply: 50/60 Hz, Voltage is shown on rating label.
 Power Consumption: 15W
 Dimensions: 434 (17-3/32") W × 122 (4-51/64") H × 320 (12-19/32") D mm
 Weight: 6.7 kg (15 lbs 4 oz)

FUNCTIONS AND DISPLAY

Functions: Direct selection, automatic search, programmed playback, repeat playback, manual search, auto space, time mode, time edit, pitch control, peak search, fader
 Display: Track number, time, music calendar, and engaged modes
 Others: Headphones jack

REMOTE CONTROL UNIT

Remote Control System: RC-235 (For Europe and U.K.)
 Power Supply: RC-234 (For U.S.A., Canada, Australia and Multi-Voltage)
 External Dimensions: 3 V DC; two R6P (standard size AA)
 Weight: dry cell batteries
 48 (1-57/64") W × 177 (6-31/32") H × 18 (45/64") D mm
 100 g (including batteries)

* Design and specifications are subject to change without notice in the course of product improvement.