



# FABORY-RIVEKLE PLUS - BLIND RIVET NUTS WITH CYL. HEAD AND KNURLE - STEEL ZINC PLATED, YELLOW PASS.

FABORY-RIVEKLE PLUS - BLINDKLINKMOEREN MET CILINDERKOP EN KARTEL - STAAL ELVZ, GEEL GEPASSIVEERD

FABORY-RIVEKLE PLUS - ECROUS NOYES MOLETES AVEC TETE CYLINDRIQUE - ACIER ELZN, PASSIVE JAUNE

FABORY-RIVEKLE PLUS - REMACHES ROSCADOS CON CABEZA CIL. Y GRAFILA - ACERO GALV. ELECTR., PAS. AMARILLO

FABORY-RIVEKLE PLUS - BLINDNIETMUTTERN MIT ZYLINDERKOPF UND RÄNDEL - STAHL VERZINKT, GELB PASSIVIERT

|                                                                                   |                                                         |                                        |                                                                                                                                |                                 |       |         |                                 |     |
|-----------------------------------------------------------------------------------|---------------------------------------------------------|----------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|---------------------------------|-------|---------|---------------------------------|-----|
|  | ISO :-<br>DIN :-<br>NEN :-<br>ANSI :-<br>BS :-<br>NF :- | GROUPCODE<br><br>YELL. P. <b>69122</b> | <br>Ordering example:<br><b>69122 4PO30</b> | M<br>St                         |       |         |                                 |     |
| Type ①                                                                            | 4PO30                                                   | 5PO30                                  | 6PO30                                                                                                                          | 6PO55                           | 8PO30 | 8PO55   | 10PO35                          |     |
| d                                                                                 | M4                                                      | M5                                     | M6                                                                                                                             | M6                              | M8    | M8      | M10                             |     |
| Grip range                                                                        | 0,5-3                                                   | 0,5-3                                  | 0,5-3                                                                                                                          | 3-5,5                           | 0,5-3 | 3-5,5   | 0,7-3,5                         |     |
| D ②                                                                               | 6                                                       | 7                                      | 9                                                                                                                              | 9                               | 11    | 11      | 13                              |     |
| B                                                                                 | 9                                                       | 10                                     | 13                                                                                                                             | 13                              | 16    | 16      | 19                              |     |
| E                                                                                 | 1                                                       | 1                                      | 1,5                                                                                                                            | 1,5                             | 1,5   | 1,5     | 2                               |     |
| s ③                                                                               | 4-1,5                                                   | 4,2-1,7                                | 4,5-2                                                                                                                          | 3,5-2                           | 5-2,5 | 5,1-2,6 | 5,4-2,6                         |     |
| L                                                                                 | 10,3                                                    | 12                                     | 13                                                                                                                             | 15,7                            | 16,5  | 19,2    | 20                              |     |
| DIMENSION CODE                                                                    |                                                         |                                        |                                                                                                                                |                                 |       |         |                                 |     |
| Type                                                                              | YELL. P.<br><b>69122</b><br>F07                         | ☒                                      | Type                                                                                                                           | YELL. P.<br><b>69122</b><br>F07 | ☒     | Type    | YELL. P.<br><b>69122</b><br>F07 | ☒   |
| 4PO30                                                                             | 040.030                                                 | 500                                    | 6PO30                                                                                                                          | 060.030                         | 500   | 8PO55   | 080.055                         | 250 |
| 5PO30                                                                             | 050.030                                                 | 500                                    | 6PO55                                                                                                                          | 060.055                         | 500   | 10PO35  | 100.035                         | 250 |
|                                                                                   |                                                         |                                        | 8PO30                                                                                                                          | 080.030                         | 500   |         |                                 |     |



# FABORY-RIVEKLE PLUS - BL. RIVET NUTS WITH FLUSH SLIM COUNTERS. AND KNURLE - STEEL ZINC PL., YELL. PASS.

FABORY-RIVEKLE PLUS - BLINDKLINKMOEREN MET LAGE VERZ. KOP EN KARTEL - STAAL ELVZ, GEEL GEPASSIVEERD

FABORY-RIVEKLE PLUS - ECROUS NOYES MOLETES AVEC TETE FRAISEE REDUITE - ACIER ELZN, PASSIVE JAUNE

FABORY-RIVEKLE PLUS - REMACHES ROSC. CON CAB. AVELL. Y GRAFILA - ACERO GALV. ELECTR., PAS. AMARILLO

FABORY-RIVEKLE PLUS - BLINDNIETMUTTERN MIT KLEINEM SENKKOPF UND RÄNDEL - STAHL VERZINKT, GELB PASS.

|                                                                                     |                                                         |                                        |                                                                                                                                  |                                 |         |        |                                 |     |
|-------------------------------------------------------------------------------------|---------------------------------------------------------|----------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|---------------------------------|---------|--------|---------------------------------|-----|
|  | ISO :-<br>DIN :-<br>NEN :-<br>ANSI :-<br>BS :-<br>NF :- | GROUPCODE<br><br>YELL. P. <b>69412</b> | <br>Ordering example:<br><b>69412 4PO30</b> | M<br>St                         |         |        |                                 |     |
| Type ④                                                                              | 4PO30                                                   | 5PO30                                  | 6PO30                                                                                                                            | 8PO30                           | 10PO35  |        |                                 |     |
| d                                                                                   | M4                                                      | M5                                     | M6                                                                                                                               | M8                              | M10     |        |                                 |     |
| Grip range                                                                          | 0,5-3                                                   | 0,5-3                                  | 0,5-3                                                                                                                            | 0,5-3                           | 0,7-3,5 |        |                                 |     |
| D ②                                                                                 | 6                                                       | 7                                      | 9                                                                                                                                | 11                              | 13      |        |                                 |     |
| B                                                                                   | 6,7                                                     | 8                                      | 10                                                                                                                               | 12                              | 14      |        |                                 |     |
| E                                                                                   | 0,3                                                     | 0,3                                    | 0,4                                                                                                                              | 0,4                             | 0,5     |        |                                 |     |
| s ③                                                                                 | 4,4-1,9                                                 | 4,8-3,3                                | 4,6-2,1                                                                                                                          | 5,5-3                           | 5,8-3   |        |                                 |     |
| L                                                                                   | 11                                                      | 13                                     | 14                                                                                                                               | 17,5                            | 21      |        |                                 |     |
| DIMENSION CODE                                                                      |                                                         |                                        |                                                                                                                                  |                                 |         |        |                                 |     |
| Type                                                                                | YELL. P.<br><b>69412</b><br>F07                         | ☒                                      | Type                                                                                                                             | YELL. P.<br><b>69412</b><br>F07 | ☒       | Type   | YELL. P.<br><b>69412</b><br>F07 | ☒   |
| 4PO30                                                                               | 040.030                                                 | 500                                    | 6PO30                                                                                                                            | 060.030                         | 500     | 10PO35 | 100.035                         | 250 |
| 5PO30                                                                               | 050.030                                                 | 500                                    | 8PO30                                                                                                                            | 080.030                         | 250     |        |                                 |     |

① Type PO cylindrical head open end and knurled shaft (for increased resistance to over-torque turning).

② Hole diameter = D + 0,1 mm.

③ s = shortening after riveting.

④ Type PO flush slim countersunk head open end and knurled shaft (for increased resistance to over-torque turning, eliminating countersunk hole preparation).